

## RADWIN 2000 C-Series

RW-2250-0200



### RW-2250-0200

RW-2250-0200 is a carrier-class radio supporting the 5.3 GHz, 5.4 GHz and 5.8 GHz bands and complying with ETSI regulations (factory default: 5.4 GHz ETSI). The multi-band radio is part of the RADWIN 2000 C-Series that delivers highest capacity and extended range for carriers' backhaul needs.

Packing native TDM and Ethernet over a single wireless link, the RADWIN 2000 C-Series provides 200 Mbps net aggregate throughput (up to 16 E1/T1plus Ethernet) at a range of up to 120 km/75 miles.

RADWIN RW-2250-0200 is connectorized for use with external antennas.

### Product Highlights

- 200 Mbps Ethernet net throughput and up to 16E1s/T1s
- Native TDM transport
- GBE support
- Single Small Form factor with embedded antenna and connectorized for external antenna
- Long range – up to 120 km/75 miles
- Adaptive asymmetric throughput – dynamic allocation between uplink and downlink
- Single radio supporting multiple bands (5.x GHz)
- Advanced MIMO, OFDM and Diversity technologies
- Robust and reliable to operate in tough conditions, extreme temperatures and non line-of-sight scenarios

**RADWIN**

## Product Specifications

Configuration	
Architecture	Outdoor Unit Connectorized for External Antenna
IDU to ODU Interface	Outdoor CAT-5e cable; Maximum cable length: 100m @100BaseT and 70m @1000BaseT
Radio	
Capacity	200 Mbps net aggregate throughput (up to 16 E1s/T1s plus Ethernet)
Range	Up to 120 km / 75 miles
Channel Bandwidth	Configurable: 10,20 or 40 MHz
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)
Adaptive Modulation & Coding	Supported
Automatic Channel Selection	Supported
Diversity	Supported
Spectrum View	Supported
Max Tx Power	5.8 GHz: 9dBm / total 36 dBm EIRP 5.4 GHz: 3.5 dBm / total 30 dBm EIRP 5.3 GHz: -3.5 dBm / total 23 dBm EIRP
Duplex Technology	TDD
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6
Encryption	AES 128
Ethernet Interface	10/100/1000BaseT
Supported Indoor Units	IDU-C Series (RW-72XX-2000), IDU-E Series (RW-71XX-1000) RADWIN PoE device (RW-9921-001X)
QoS	Packet classification to 4 queues according to 802.1p and Diffserv, Dynamic scheduling according to air interface changes
VLAN	Supported
Ethernet Ring Protection	Supported, including Ethernet 1+1
Hub Site Synchronization (HSS)	Up to 16 collocated links (RADWIN 2000 and/or WinLink 1000)
Monitored Hot Standby (MHS)	1+1 with RADWIN 2000 link or WinLink 1000 link

Supported Bands		
Band	Occupied Frequency Range	Radio Compliance
5.8 GHz ETSI	5.735 – 5.865	ETSI EN 302 502
<b>5.4 GHz ETSI*</b>	<b>5.480 – 5.715</b>	<b>ETSI EN 301 893</b>
5.3 GHz ETSI	5.160 – 5.340	ETSI EN 301 893

### \* Factory Default

Mechanical	
Dimensions	19.5(w) x 27.0(h) x 8.0(d) cm
Weight	1.8 kg / 3.6 lbs
Power	
Power Feeding	Power provided over ODU-IDU cable
Power Consumption	<35W (IDU + ODU)
Environmental	
Operating Temperatures	-35°C - 60°C / -31°F – 140°F
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1m)
Safety	
FCC/IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22
ETSI	EN/IEC 60950-1, EN/IEC 60950-22
EMC	
FCC	CFR47 Class B, Part15, Subpart B
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4
CAN/CSA-CEI/IEC	CISPR 22-04 Class B
AS/NZS	CISPR 22-2004 Class B

## Ordering Information

**Part Number:** RW-2250-0200

### Description:

RADWIN 2000 C-Series ODU Connectorized for external antenna (2x N-type), supporting multi frequency bands at 5.x,

Factory default 5.4 GHz ETSI

**Corporate Headquarters,** T. +972.3.766.2900, E. sales@radwin.com, www.radwin.com

The RADWIN name is a registered trademark of RADWIN Ltd.

© All rights reserved, July 2011

DS RW-2250-0200/07.11