

2010-2SW-FS

Centrales analógicas: licencia de servidor para aplicación móvil App Fire-2 Mobile.

FiRe Server Application

The 2010-2 fire panels allow external connections via an SDK (Software Development Kit) as well as connections from mobile devices like iPhone, iPad, Android & windows phones. The communication between the panel and the mobile devices is provided by the FiRe application server, which allows setting up users, configuring panel features, handles the authentication and can act as a firewall for the connected clients. The communication between the FiRe server and mobile application is based on a modern RESTless/REST (REpresentational State Transfer) interface. The provided mobile application allows the basic functionality of checking system status and basic control. The additional features OMWT (One Man Walk Test) and output tests streamline the installation and maintenance process. The mobile application is available in 12 languages for easier installer usage and acceptance. The application is activated by use of a USB dongle, to be installed on the server running the FiRe server application.



Details

- Check status of the system
- Check and confirm notifications
- Check panel history event log
- Basic control : reset, sound/silence, enable/disable devices, show LED to find device
- OMWT (One Man Walk Test)
- Output test
- Compatible with panels as of firmware version 3.5

2010-2SW-FS

Centrales analógicas: licencia de servidor para aplicación móvil App Fire-2 Mobile.

Technical specifications

Físico

Dimensiones físicas	135 x 38 x 140 mm (W x H x D)
Peso neto	21 g
Peso de envío	100 g



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 8 December 2021 - 10:23