

N-MC-FE

MCP Accessory - Intelligent Manual Call Point Frangible Element

General

The N-MC-FE is a glass trigger element for compatible, Type-A series manual call points. It may be used as alternative for resettable elements that are normally used in these manual call points. The N-MC-FE allows the manual call point to be easily activated without the need for tools.

Visual Indication


The N-MC-FE uses clear black print on a brilliant white background. An arrow on either side pointing inwards towards a dot indicates to the operator where to push on the element to activate the manual call point.

Easy to Install

Installation of the frangible element in a compatible manual call point is made easy by the design of the manual call point. Using the test key the front cover of the manual call point is removed, allowing the insertion of the N-MC-FE with a quick and simple action.

Safe to Use

The coated glass element is designed to break easily and safely across a vertical running break guide, consistently in the same place. Little force is required to break the element, eliminating the need for special tools to facilitate activation. The glass coating ensures no splintering of the glass, avoiding possible injury to the operator during the activation process.



Details

- Quick installation without special tools
- Easy to retrofit
- Coated glass prevents operator injury by controlling the glass break and avoiding glass fragments
- Easy break glass for smooth and consistent breaks in the same position
- Easy to operate without the need for hammers
- EN54 certified with compatible manual call points

N-MC-FE

MCP Accessory - Intelligent Manual Call Point Frangible Element

Technical specifications

General

Interfaz de usuario	Printed
Compatibilidad	ActivSense manual call points

Físico

Dimensiones físicas	1 x 76 x 45 mm (W x H x D)
Peso neto	15.7 g
Color	Blanco
Material	Cristal
Marcado funcional	→●←

Medioambiental

Antivandálico	No
Temperatura de funcionamiento	-30 to +72°C
Temperatura de almacenamiento	-30 to +72°C
Humedad relativa	10 to 95% (noncondensing)
Entorno	Interior, Exterior

Estándares y regulaciones

Cumplimiento	REACH, RoHS 2, WEEE
Normativas	EN54-11

