

FE260-475

Retenedor electromagnético de 400N para montaje en suelo/pared con pulsador de desbloqueo.

General

The FE260-475 is a floor/wall mount door holder with a universal adjustable tube with a reach of 475 mm when used in 180° configuration and 450 mm used in 90° configuration. Which offers a 400N holding force and a release button.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Adjustable

The “head” of the FE260-475 allow for two mounting options. The first being the 180° configuration, which is normally used when the door holder is mounted on the wall. In this configuration, the magnet is located “on-top” of the tube.

And the second configuration being the 90° configuration, which is normally used when the door holder is mounted on the ground. In this configuration, the magnet is located on the “side” of the tube, as shown in the picture.

To allow for even more flexibility, the tube can also be cut shorter to match the exact distance required.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The base is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE260-475 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- Release button
- EN1155 approved
- Adjustable
- Keeper plate included

FE260-475

Retenedor electromagnético de 400N para montaje en suelo/pared con pulsador de desbloqueo.

Technical specifications

General

Fuerza de retención N 400
(Newtons)

Botón de liberación Si

Diodo de supresión de chispa Yes

Protección contra inversión de polaridad Yes

Eléctrico

Tipo de fuente de alimentación 24 VCC

Consumo de corriente 1.6 W

Ciclo de trabajo 100%

Físico

Dimensiones físicas 80 x 90 x 450 mm (W x H x D) 90° setup
80 x 90 x 475 mm (W x H x D) 180° setup

Medioambiental

Clasificación IP IP54 (Magnet)

Estándares y regulaciones

Normativas EN1155

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 3 June 2020 - 8:25

